

SECTION 6.**ACCIDENTAL RELEASE MEASURES**

Not Applicable for product in its purchased form.

SECTION 7.**HANDLING AND STORAGE**

Store supported and protected from direct contact with the ground in a well ventilated, cool, dry place, away from open flames or unstable temperatures. Moisture causes wood to warp and may damage product. High temperatures may cause the product to ignite or cause smoldering combustion.

Handle with a firm grip on the cabinet to avoid damages. Do not let cabinet bang or contact the floor on the corners.

SECTION 8.**EXPOSURE CONTROLS/PERSONAL PROTECTION**

Personal Protective Equipment: General: The articles, as shipped, do not require personal protective equipment. Follow good hygienic and housekeeping practices. Clean up areas where dust settles to avoid excessive accumulation of combustible materials. Use appropriate PPE (Safety Glasses, Hearing Protection, Gloves) if cutting, sanding or machining the articles.

SECTION 9.**PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Cabinets, various sizes & colors	Odor:	Resinous wood odor
Physical State:	Solid	pH:	Not Available
Vapor Pressure:	Not Applicable	Vapor Density:	Not Applicable
Boiling Point:	Not Applicable	Melting Point:	Not applicable
Solubility (H₂O):	Insoluble	Specific Gravity:	Variable - depending on moisture content

SECTION 10.**STABILITY AND REACTIVITY**

Chemical Stability: This product is stable under ordinary conditions of use.

Chemical Stability/Conditions to Avoid: Avoid excess heat, open flames and sparks in direct contact.

Incompatibility: Avoid contact with oxidizing agents and drying oils.

Hazardous Decomposition: Burning wood produces irritating and toxic fumes and gasses.

SECTION 11.**TOXICOLOGICAL INFORMATION**

Wood Dust: Wood dust generated from sawing, sanding, or machining may cause nasal dryness, irritation, coughing and sinusitis. IARC and NTP classify wood dust as a carcinogen. This classification is based on the increased occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust above certain thresholds. The conditions are not present in the article as sold to the consumer.

SECTION 12.**DISPOSAL CONSIDERATIONS**

This product is not considered hazardous waste under Federal Hazardous Waste Regulations 40 CFR 261. Please be advised State and Local requirements for waste disposal may be different from federal regulations.

You should recycle if possible. Incinerate or landfill in accordance with local, state or federal regulations.

SECTION 13.**TRANSPORT INFORMATION**

This product is not regulated as a hazardous material by United States (DOT) or Canadian (TDG) transportation regulations.

SECTION 14.**REGULATORY INFORMATION**

OSHA: Wood products and components are not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, wood dust generated by sawing, sanding or machining these products may be hazardous.

TSCA: This product complies with TSCA inventory requirements

SARA 313: None.

CANADIAN WHMIS: These products are not considered controlled products.

SECTION 15.

OTHER INFORMATION

H. U. D. This product complies with H.U.D. regulation 24 CFR Part 3280 as emissions of formaldehyde is well below the maximum large chamber test requirement of 0.3 ppm.

California Proposition 65: Safe Drinking Water and Toxic Enforcement Act: Title 22 California Code of Regulations California Proposition 65 provides for labeling and disclosure of the presence of chemical(s) known to the State of California to cause cancer or reproductive toxicity. This product contains Formaldehyde in extremely low levels and may, depending on conditions, emit Formaldehyde. Based on testing data (emissions of 0.03 ppm) and recognition by OSHA that .75 ppm TWA is a safe exposure level, we do not feel that exposure to this product presents significant risk to users.

SARA 313: This product does not contain chemical(s) in concentrations requiring reporting under SARA 313.

ODS: During the manufacture of this product, there was no use of ozone depleting substances as defined in EPA regulations.

N.A.H.B.: Compliant with 2005 National Association of Home Builders Green Home guidelines program.

IMPORTANT: Grandview Products Company believes the information contained in this MSDS to be accurate at the time of preparation and it has been compiled using testing and sources believed to be reliable. However, Grandview Products makes no warrant, either expressed or implied concerning the accuracy or completeness of the information presented. The implied warranties of merchantability and fitness for a particular purpose are specifically excluded. It is the responsibility of the user to research and comply with local, state, or federal regulations concerning the use, storage, handling and disposal of this product.

MSDS History:

Effective Date: 9/12/2007
Supersedes Date: 12/21/89
Revision Date: None

Preparer: Joe S. Wright **REM, CPEA**
Grandview Products Company
E. H. & S. Manager

TEST NOTE: Formaldehyde testing was completed 2/2/07 at the request of KCMA on a 30"x30" wall cabinet and a 30" base cabinet. The tests were conducted under ASTM E 1333 Large Scale Test Chamber conditions. Pinnacle cabinets emitted 0.03ppm and Piedmont emitted 0.06ppm. This equates that a typical residence (1,790 sq. ft.) could install 50+ base cabinets and 50+ wall cabinets without exceeding the 0.1ppm exposure limits. The complete testing data is on file at our facility.

Recycle for the Environment

